

The **Enhanced Tactile Release** (ETR-940) is designed for use with Mossberg 940 series shotguns that are factory drilled/tapped for an enlarged bolt release.

BEFORE YOU BEGIN:

Make absolutely sure that your shotgun is unloaded before installation of the ETR. Ensure there are no rounds in the magazine tube and that the chamber has been visually inspected to make sure it is clear. Ensure the bolt is closed as well.

INSTALLATION:

The ETR re-uses the factory screw and installs directly in place of the existing factory bolt release button. Your OEM shell stop assembly should be clean and free of debris before installation of the ETR.

Seat the Enhanced Tactile Release over the factory shell stop's button. Hand tighten the factory screw with the appropriate sized key for the OEM screw.

Once you have tested the part for proper function and are satisfied with position, you can disassemble the part, apply a drop of blue thread locking compound to the screw threads and reassemble. Hand-tighten with key. Do NOT over tighten!

MAINTENANCE:

After the first 100 rounds, check that the Tactile Bolt Release hasn't rotated or otherwise moved. Finish wear may develop in areas that come in contact with the receiver. This is normal and will not affect function of the ETR-940 or shotgun.

Refer to our website for any updates to installation or maintenance procedures.



www.OR3GUN.com

Made in the USA